



TDRBRAVO

REINFORCED CONCRETE PIPE



TDRPIPE

TDR™ BRAVO is our reinforced concrete pipe product line. Designed specifically for your culvert and storm drain projects. TDR™ BRAVO uses top-tier materials to ensure unmatched strength. With its leakproof and watertight joint, expect superior hydraulic performance every time.



SCOPE

This fact sheet describes 18" through 84" TDR™ BRAVO reinforced concrete pipe for use in concrete culverts and storm drains.

PIPE

TDR™ BRAVO pipe is a product with exceptional strength, water-tightness security and advanced technology.

- Concrete pipe is non-flammable product
- Lower embedment material cost
- No excess deflection concerns
- Reduces likelihood of floatation
- Type-B wall, available in classes II, III, IV and V

APPLICATIONS

- Concrete Culvert
- Highway Drainage
- Storm Drain

STANDARDS

- ASTM C76
- ASTM C443

ID	Wall Thickness	Weight	Pipe Length
in	in	lb/ft	ft
18"	2.40"	190	8.0'
24"	3.00"	288	
30"	3.50"	402	
36"	4.00"	547	
42"	4.50"	718	
48"	5.00"	905	
60"	6.00"	1355	
72"	7.00"	1894	
84"	8.00"	2548	

O-Ring JOINT

100% Watertight Gasketed Joint

